

Order no.: 154347

Mobile scaffolding,
0.75 × 1.80 m, with
chassis bar. Platform
height 3,26 m



Accessories for the product family



Order no.: 027992

Safety railing for
mobile scaffolding



Order no.: 027905

Push-fit frame, 0.75
m. Height: 1.00 m



Order no.: 027904

Push-fit frame, 0.75
m. Height: 2.00 m



Order no.: 027918

Push-fit frame, 0.75
m. Height: 0.5 m



Order no.: 027955

Railing lengthwise
1,800 mm



Order no.: 027931

Platform with
trapdoor For
scaffolding length:
1.8 m



Order no.: 027913

Toe board front
side For scaffolding
width: 0.75 m



Order no.: 027943

Toe board long side
For scaffolding
length: 1.8 m



Order no.: 027937

Diagonal brace 1.8
m



Order no.: 027935

Horizontal strut For
scaffolding length:
1.8 m



Order no.: 027923

Chassis bar 2 m



Order no.: 027917

Swivel castor with spindle height adjustable Ø 200 mm




Order no.: 027940

Step-on bracket



Order no.: 027912

Ballast weight with hanging brackets RAL 1021



Order no.: 019081

Clip tray for tubes Ø 50 mm



Order no.: 027920

Wall spacer adjustable Adjustable up to 1.0 m



Order no.: 070506

Frame extension can be clamped on Adjustment range max. 400 mm



Order no.: 019274

Storage tray 500 x 220 mm Clamping range 38–51 mm



Order no.: 019276

Storage tray 800 x 300 mm Clamping range 38–51 mm



Order no.: 019175

Inspection sticker 40 x 40 mm



Order no.: 019176

Inventory sticker



Order no.: 070507

Safety door on front side Push-fit frame 0.75



Order no.: 070505

Scaffolding connector set For scaffolding width: 0.75 m



Order no.: 019136

Spring clip for mobile scaffolding with short pin, closed



Order no.: 070524

Scaffolding strut telescopic 1,700–2,500 mm



Order no.: 027104

**Height-adjustable
spindle**



Order no.: 027922

**Swivel castor with
spindle, non-
marking grey height
adjustable Ø 200
mm**



Order no.: 027921

**Swivel castor with
spindle, electrically
conductive height
adjustable Ø 200
mm**



Order no.: 027958

**Swivel castor Ø
200 mm With
parking brake and
pin**