

Order no.: 125150

## FlexxTower SGX

Platform height [mm]

**7550**

### Specification

Working height 9.55 m	Scaffolding height 8.82 m	Platform height 7.55 m	Platform width 600 mm	Platform length 1.8 m
Load capacity 2 kN/m <sup>2</sup>	Weight 208 kg	Transport dimensions 1850 x 800 x 850 mm, 208 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation possible & allowed
Outdoor use, central installation possible & allowed	Outdoor use, lateral installation possible & allowed	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, indoor, lateral installation 0 kg	Ballasting of scaffolding, outdoor, central installation 90 kg
Ballasting of scaffolding, outdoor, lateral installation 90 kg	Ballasting per outrigger, indoor, central installation 20 kg	Ballasting per outrigger, indoor, lateral installation 20 kg	Ballasting per outrigger, outdoor, central installation 50 kg	Ballasting per outrigger, outdoor, lateral installation 50 kg
Business division MUNK Günzburger Steigtechnik	Order no. 125150	Price € 8,300.00		

### Facts

- Mobile scaffolding made of sturdy aluminium tubing with welded frame parts
- For lower workplaces, the scaffolding can also be assembled at lower heights

- Secured on all sides thanks to leading railing; can be assembled and dismantled from level to level by one person (can be used by up to two people)
- Tool-free assembly thanks to push-fit connectors and quick-release connectors
- Easy to handle thanks to individual lightweight parts
- Excellent flexibility and stability, thanks to fold-out triangular outrigger with swivel base – also ideal for wall mounting or moving in narrow passages
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m<sup>2</sup>
- With integrated ergo platform with flap

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



### Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



### Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



### Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools




### Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



### Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



#### Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

