



Order no.: 036006

Rung straight ladder  
made of glass-fibre  
reinforced plastic without  
stabiliser



Number of rungs

- 6    8    10    12    14

## Specification

Working height 3 m	Step design Rungs	Number of steps/rungs 6 rungs	Step/Rung height 29 mm	Step depth 28 mm
Step/Rung distance 280 mm	Ladder length 1.92 m	Outer width 420 mm	Depth of side-rails 73 mm	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type To lean against	Weight 6 kg	Transport dimensions 1920 x 425 x 75 mm, 6 kg	Business division MUNK Günzburger Steigtechnik
Order no. 036006	Price € 379.00			

## Facts

- Rung straight ladder made of reinforced fibre glass
- Side-rails and rungs made of reinforced fibre glass plastic profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 28,000 V as per DIN EN 61478:2002 Category 1
- nivello® ladder shoes with patented 2-axis inclination technology
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)
- Note: Products with glass-fibre reinforced plastic content are non-returnable due to their sensitivity

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

The movable ladder shoe sets new standards in stability

[Learn more](#)



### Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



### Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



## Certificates

---



17KFP1938-02 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-3:2007  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1(PAH-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK  
EK5/AK1 17-1:2017  
DIN EN 131-1:2016  
DIN EN 131-2:2017

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

