



Order no.: 036812

Rung straight ladder
made of glass-fibre
reinforced plastic with
stabiliser



Number of rungs

12

14

Specification

Working height 4.7 m	Step design Rungs	Number of steps/rungs 12 rungs	Step/Rung height 29 mm	Step depth 28 mm
Step/Rung distance 280 mm	Ladder length 3.59 m	Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 73 mm
Width of side-rails 25 mm	Max. load capacity 150 kg	Design type To lean against	Weight 11.94 kg	Transport dimensions 3560 x 430 x 90 mm, 11.94 kg
Business division MUNK Günzburger Steigtechnik	Order no. 036812	Price € 872.00		

Facts

- Rung straight ladder made of reinforced fibre glass
- Side-rails and rungs made of reinforced fibre glass plastic profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Tested up to 28,000 V as per DIN EN 61478:2002 Category 1
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Certificates



17KFP1938-02 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-3:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5/AK1 17-1:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

