

Order no.: 116101

## Scaling ladder lower section ÖNORM F 4047



### Specification

|                                  |   |  |  |                       |
|----------------------------------|---|--|--|-----------------------|
| Intended use<br>Rescue           | Ladder length<br>2.7 m                                | Setting angle<br>70 °                        | Clear width between<br>rungs<br>245 mm | Outer width<br>483 mm |
| Ladder feet<br>Ladder shoe       | Depth of side-rails<br>74 mm                          | Width of side-rails<br>35 mm                 | Step/Rung height<br>28 mm              | Step depth<br>29 mm   |
| Number of steps/rungs<br>9 rungs | Step/Rung distance<br>273 mm                          | Max. load capacity<br>216 kg                 | Persons max.<br>2                      | Material<br>Aluminium |
| Weight<br>8.6 kg                 | Transport dimensions<br>2660 x 484 x 85 mm,<br>7.5 kg | Business division<br>MUNK<br>Rettungstechnik | Order no.<br>116101                    |                       |

### Facts

- Rescue ladder, made of aluminium, compliant with ÖNORM F4047
- Secure push-fit connections with spring-loaded locking pin
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance

- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- Upper ladder with box profile rung made of aluminium chequered plate
- Permissible load: 2 persons

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

