



Order no.: 068239

Connecting brace

Specification

Length 1 m

Material Stainless steel Transport dimensions 1000 x 70 x 40 mm, 2.5 kg Business division MUNK Günzburger Steigtechnik Order no. 068239

Facts

- For reinforcing ladder sections if, contrary to the standard, the spacing of the wall anchors is larger than 2.0 m for construction reasons
- Made of stainless steel
- Two stuccos are required per ladder connection point
- If the back guard is mounted in the area of the connecting struts, clamps Clamps order no. 68240 are required

Scope of supply

■ Brace: 1 x

Installation material: 1 x



Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria







