

Order no.: 063499

Access guard can be hooked in



Specification

Material Aluminium Transport dimensions 1190 x 538 x 59 mm, 6 kg Business division MUNK Günzburger Steigtechnik Order no. 063499

Facts

- Effectively protects vertical ladders against unwanted access by unauthorised persons
- Simple to hook into the rungs thanks to rear profiles
- The lock is comprises a security bolt and the supplied padlock (incl. two keys)
- Height: 1,190 mm
- Width: 536 mm
- Distance from entrance level to lower edge of back protection min. 2,700 – max. 3,000 mm in accordance with DIN 18799-3



Scope of supply

- Lockable access barrier: 1 x
- Assembly instructions: 1 x

Installation material: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures



Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria

